

TYPE 67CFR REGULATOR FAST Europe

1/4 NPT aluminum body and spring case with integral 5 micron polyethylene filter and internal relief valve. Two outlets tapped. Nitrile valve plug and brass valve stem. Standard construction places brass drain valve under inlet and vent over the inlet. Pressure gauges have brass wetted parts and plastic case. Approximate shipping weight is 1 pound. 10 units per shipping carton. For stainless steel bodies refer to Type 67CFSR price pages. **Mounting Spacers no longer supplied, see option if required.**

RANGE, psig	FILTER	PRESSURE GAUGE, psig / MPa / bar	ADJUSTING SCREW	FS NUMBER	LIST PRICE
0 to 20	5 micron polyethylene	None	Square	67CFR-585 ♦	\$ 136
	5 micron polyethylene	0 to 30 / 0 to 0,2 / 0 to 2	Square	67CFR-260 ♦	159
0 to 35	5 micron polyethylene	None	Square	67CFR-224 ♦	136
	5 micron polyethylene	None	Square	67CFR-581 ⁽¹⁾ ♦	136
	5 micron polyethylene	None	Square	67CFR-362 ⁽²⁾ ♦	136
	5 micron polyethylene	None	Square	67CFR-584 ⁽³⁾ ♦	136
	5 micron polyethylene	None	Square	67CFR-579 ⁽⁴⁾ ♦	136
	5 micron polyethylene	0 to 30 / 0 to 0,2 / 0 to 2	Square	67CFR-235 ♦	159
	5 micron polyethylene	0 to 30 / 0 to 0,2 / 0 to 2	Handwheel	67CFR-241 ♦	183
	5 micron polyethylene	0 to 60 / 0 to 0,4 / 0 to 4	Square	67CFR-206 ♦	159
	40 micron SST	None	Square	67CFR-24	180
	40 micron SST	0 to 30 / 0 to 0,2 / 0 to 2	Square	67CFR-35	204
	40 micron SST	0 to 60 / 0 to 0,4 / 0 to 4	Square	67CFR-59	204
	0 to 60	5 micron polyethylene	None	Square	67CFR-225 ♦
5 micron polyethylene		None	Square	67CFR-582 ⁽¹⁾ ♦	136
5 micron polyethylene		None	Square	67CFR-600 ⁽²⁾ ♦	136
5 micron polyethylene		None	Square	67CFR-580 ⁽⁴⁾ ♦	136
5 micron polyethylene		0 to 60 / 0 to 0,4 / 0 to 4	Square	67CFR-237 ♦	159
40 micron SST		None	Square	67CFR-50	180
0 to 125	40 micron SST	0 to 60 / 0 to 0,4 / 0 to 4	Square	67CFR-40	204
	5 micron polyethylene	None	Square	67CFR- 226 ♦	136
	5 micron polyethylene	None	Square	67CFR-583 ⁽¹⁾ ♦	136
	5 micron polyethylene	None	Square	67CFR-601 ⁽²⁾ ♦	136
	5 micron polyethylene	0 to 160 / 0 to 1,1 / 0 to 11	Square	67CFR-239 ♦	159
	40 micron SST	None	Square	67CFR-26	180
	40 micron SST	0 to 160 / 0 to 1,1 / 0 to 11	Square	67CFR-38	204

1. Drain valve is opposite side outlet connection, vent is over inlet.
 2. Drain valve is under outlet, vent is over outlet.
 3. Drain valve and vent opposite side outlet.
 4. Drain valve under side outlet, vent over inlet.

TYPES 67CF AND 67CFR OPTIONS AND LIST PRICE EXTRAS

Construction Variations

CONSTRUCTION	OPTION NUMBER	LIST PRICE EXTRA
Polyvinylidene fluoride (PVDF) filter 40 micron ⁽¹⁾	PF	\$ 0
Stainless steel filter 40 micron ⁽¹⁾	SF ♦	44
Glass filter 5 micron ⁽¹⁾	GF ♦	11
Handwheel adjusting screw ⁽²⁾	K ♦	24
Aluminum valve plug stem	VS	21
Fluorocarbon diaphragm ⁽³⁾	V	45
Fluorocarbon valve plug (includes aluminum valve stem) ⁽³⁾	VP	21
Stainless steel valve stem (includes nitrile valve plug)	SSS	84

1. Apply only to FS numbers with polyethylene filters.
 2. Apply only to FS numbers with square head adjusting screw.
 3. If operating temperature is above 180°F - add filter option (PF, SF, or GF).

- continued -